




GD500 Z/ZP 12-24m/min



GD58002722P Material Hoist / Transport Platform




Platform Versions:






An ingenious system: you can use the GEDA UNI-MAST for all GEDA rack and pinion hoists from 300kg to 2000kg load bearing capacity.

Flexible and economic working with only one mast system!







Only put together the 1.5m mast sections and screw them with captive screws and safety nuts.





Technical Data - GD500 Z/ZP

CAPACITY

Payload	850kg
Lifting Speed	12-24
Counter Weight	No
Maximum Lifting Height	100m

ELECTRICAL DATA

Motor Power Supply 230 V power on platform Overload device Automatic lubrication

DIMENSIONS & WEIGHT

Transport dimensions (L X W) Platform A Platform B Platform C

HOIST CONTROLS

Manual controls / Erection controls Drop test controls Programmable landings Hoist calling system

GENERAL

Finishing Cabin / Ground Enclosure Company Logo & Colour Ground Enclosure Cable System Erection Jib Norms & Regulations 850kg 12-24m/min No 100m

1 x 3.0/6.1Kw/16A 400V - 50hz, 3p Standard, included Standard, included Standard, included

1.6 x 1.4m 1.6 x 1.4m 1.6 x 1.4m

Standard, Included Standard, Included Optional Optional

Galvanised / Powder Coated Optional Basket Optional European Machine Directive CE 2006/42 EC Australian Standards

*Data based on a standard configuration

GEDA products have been sold in 80 different countries around the world. In addition to our subsidiaries in Germany, Russia, the USA and Turkey, our comprehensive dealer network plays a huge part in our worldwide success. GEDA is represented both in Europe and in the Pacific region through skilled professional dealers who are responsible both for sales and service in their local areas.

21-29 West Circuit, Sunshine West, 3020 VIC, AUSTRALIA P. +61 3 9312 6497E. sales@scanrent.com.auwww.scanrent.com.au

